



TSU ACE

Low Cost T1/FT1 DSU/CSU

Product Features

- Single V.35 DTE interface
- Nx56 or Nx64 operation for data rates to 1.536 Mbps
- Auto and Manual D4(SF) or ESF framing support
- B8ZS or AMI line coding
- Easy to use front panel keypad for unit configuration
- Remote configuration from host TSU via FDL or 8k in-band
- Local and remote loop-back capability
- Extensive built in test capabilities
- Standard five-year warranty


The ADTRAN TSU ACE is a low cost, full-featured T1/FT1 Data Service/ Channel Service Unit (DSU/CSU). The TSU ACE provides an interface between T1 or Fractional T1 service and the end user's Data Terminal Equipment (DTE) for applications such as LAN-to-LAN bridging, Frame Relay circuit termination and video-conferencing. The TSU ACE provides access to traditional dedicated point-to-point T1 services as well as network termination for Frame Relay.

Housed in a compact, durable plastic housing the TSU ACE supports synchronous data rates from 56 kbps to 1.536 Mbps at Nx56 or Nx64 kbps. A single V.35 physical interface provides a connection to the end user's DTE equipment.

For configuration and testing, the TSU ACE provides the capability for remote control from a host TSU through the T1 FDL channel. If the FDL channel is unavailable, the host TSU can use 8 kbps of the data traffic to provide configuration and control of the remote TSU ACE. The in-band control channel is used on an as needed basis and is automatically controlled by the host TSU.

The TSU ACE responds to standard local and remote loopback commands from the telephone company central office. In addition, the user has several built-in test capabilities including V.54 remote loopback and 511 BERT test patterns. Complete configuration and performance data is available from the front panel keypad and two-line by 16 character LCD display.

ADTRAN provides several T1 DSU/CSUs for a variety of customer applications. Additional products in the TSU family include the TSU LT, TSU ESP, TSU100, TSU120, TDU120 and the TSU600. These T1/FT1 DSU/CSUs offer flexibility, modularity and end user configuration. The modular approach allows the ADTRAN TSU family to serve in point to point T1 applications with a mixture of voice, data and video.



ADTRAN





ADTRAN, Inc.

Attn: Enterprise Networks
901 Explorer Boulevard
Huntsville, AL 35806

P.O. Box 140000
Huntsville, AL 35814-4000

256 963-8000 voice
256 963-8699 fax
256 963-8200 fax back

General Information

800 9ADTRAN
info@adtran.com
www.adtran.com

Pre-Sales

Technical Support

800 615-1176 toll-free
application.engineer@adtran.com
www.adtran.com/support

Where to Buy

877 280-8416 toll-free
channel.sales@adtran.com
www.adtran.com/where2buy

Post-Sales

Technical Support

888 423-8726
support@adtran.com
www.adtran.com/support

ACES Installation & Maintenance Service

888 874-ACES
aces@adtran.com
www.adtran.com/support

International Inquiries

256 963 8000 voice
256 963-6300 fax
international@adtran.com
www.adtran.com/international

For the regional office nearest you, visit:

www.adtran.com/where2buy



I.S. EN ISO 9001
ADTRAN is a
ISO 9001 registered company.



TL 9000
ADTRAN is a
TL 9000 registered company.

Printed in the U.S.A.
61200295L1-8A May 2002
©2002 ADTRAN, Inc. All rights reserved.

TSU ACE

Low Cost T1/FT1 DSU/CSU

Product Specifications

Network Interface

Line Rate

- T1/FT1 (1.544 Mbps)

Physical Interface

- RJ48C: 8-Pin Modular

Framing

- SF/ESF
- Auto Detection

ESF Format

- AT&T 54016
- ANSI T1.403

Line Code

- AMI/B8ZS

Input Signal

- 0 to -36dB

DSO Assignment

- Contiguous
- Alternating

T1 Transmit Timing

- Loop Timed
- Internal
- DTE

DTE Interface

Bit Rate

- 56 kbps to 1.536 Mbps,
Nx56 or Nx64 kbps (N=1 to 24)

Electrical

- CCITT V.35

Mechanical

- V.35 (Winchester Type 34 pin)

DTE Transmit Clock

- Automatic

Performance Monitor & Data

- BPVs/CRCs, ES, SES, UAS, % AS,
% EFSEC, Alarms, Errors

Reports

- NI information stored for last 24 hours in
15 minute increments



Specifications subject to change without notice. ADTRAN is a trademark of ADTRAN, Inc. All registered trademarks and trademarks mentioned in this publication are the property of their respective owners.

PRMS

- ANSI Performance Report Messages
(User selectable)

Tests

Local

- Payload/Line Loopback, DTE Loopback

Remote

- Payload/Line Loopback, V.54 (DTE) Loopback

Network

- CSU and DSU loopbacks

Built-In Test Patterns

- 511 (active DS0s) with error insert available
- 1:8 (all DS0s)
- All 1's (all DS0s)
- All 0's (all DS0s)

Remote Configuration

Required Software

- ADTRAN T-Watch Pro™

Required Hardware (one of the following)

- TSU LT (1202060L1)
- TSU (1200060L2)
- TSU RM (1202077L1)
- TSU ESP (1200169L1)

Agency Approvals

- FCC part 15, Class A, FCC Part 68,
Industry Canada CS03, UL, CUL

Environment

Operating Temperature

- 0 to 50°C, (32 to 122°F)

Storage Temperature

- -20 to 70°C, (-4 to 158°F)

Relative Humidity

- Up to 95%, non-condensing

Physical

Dimensions

- 1.5" H, 6.25" D, 9" W

Weight

- 2 lbs

Power

- 115VAC, 60Hz, 5W

Ordering Information

Equipment	Part #
TSU ACE	1200295L1



Sold by:

TWAcomm.com
http://www.TWAcomm.com
Toll Free: (877) 892-2666