

## Dimensions

Part Number	Description	Overall Size			Cable Opening		Hole in Floor	
		Height	Width	Depth	Width	Depth	Width	Depth
13870-00X	KoldLok Wave™ Split Integral Grommet	1-7/8" (48 mm)	11" (279 mm)	9" (229 mm)	7-3/4" (197 mm)	5-7/8" (149 mm)	9-1/4" (235 mm)	6-3/4" (172 mm)
13571-00X	Integral Grommet	1-5/8" (41 mm)	11" (279 mm)	8-1/4" (210 mm)	8" (203 mm)	4" (102 mm)	9-1/4" (235 mm)	6-3/4" (172 mm)
13671-00X	Split Integral Grommet	1-5/8" (41 mm)	11" (279 mm)	8-1/4" (210 mm)	8" (203 mm)	4" (102 mm)	9-1/4" (235 mm)	6-3/4" (172 mm)
13576-00X	Surface-Mount Grommet	1-1/8" (29 mm)	11" (279 mm)	8-1/4" (210 mm)	8-1/4" (210 mm)	4" (102 mm)	10" (254 mm)	7-1/4" (184 mm)
13676-00X	Large Surface-Mount Grommet	1-15/16" (33 mm)	12" (305 mm)	11-3/4" (298 mm)	8-1/4" (210 mm)	4" (102 mm)	10" (254 mm)	9-3/4" (248 mm)
13677-00X	Extra-Large Surface-Mount Grommet	1-15/16" (33 mm)	12" (305 mm)	15" (381 mm)	8-1/4" (210 mm)	4" (102 mm)	10" (254 mm)	13" (330 mm)
13674-00X	Extended 3" (76 mm) Brush Grommet	1" (25 mm)	24" (610 mm)	4" (102 mm)	22" (559 mm)	2-1/2" (64 mm)	22" (559 mm)	2-1/2" (64 mm)
13675-00X	Extended 6" (152 mm) Brush Grommet	1" (25 mm)	24" (610 mm)	7" (178 mm)	22" (559 mm)	5-1/2" (140 mm)	22" (559 mm)	5-1/2" (140 mm)
13872-00X	Mini Grommet	1-1/2" (38 mm)	7-11/16" (195 mm)	5-11/16" (144 mm)	5" (127 mm)	2-1/2" (64 mm)	6" (152 mm)	4" (102 mm)

## Fan Kit For M-Series MegaFrame



The MegaFrame Fan Kit provides optional ventilation and cooling for the cabinet.

- Four fans mount on two interchangeable frames to fit cabinet top panel
- Grill design and ball-bearing motor offer longer life and quiet operation
- Each fan frame has an IEC C-14 power inlet
- Includes a detachable 15'L (4.6 m) power cord with a molded plug
- Provides up to 400 CFM of ventilation for cabinet
- Can be used on the MegaFrame, SlimFrame and Seismic Frame Cabinets
- UL Recognized

Part Number	Description / Color	Shipping Weight lb (kg)
<b>Cooling Fan Kit - 400 CFM</b>		
12480-701	Black, 115 VAC, 50/60 Hz, NEMA 5-15P	6 (2.7)
12480-702	Black, 230 VAC, 50/60 Hz, NEMA 6-15P	6 (2.7)

### Fan Specifications - Each Fan

Operating Voltage	Airflow	Noise Level (1 Meter Max)	Power Consumption	Operating Frequency
115 VAC	100 CFM	37 dBA	15 Watts	50/60 Hz
230 VAC	100 CFM	37 dBA	15 Watts	50/60 Hz